



 SPOC 5342

EN ISO 20347:2012 02, A, E, FO, SRC ASTM F2892-18 SD 35



[Learn more](#)

OCCUPATIONAL SHOE FOR DIFFERENT JOBS

A comfortable, certified and good-looking occupational shoe for many different jobs in different industries. Shock-absorbing soles in multiple layers provide personal protection. Upper material in full-grain leather. The sock-like construction improves comfort. The shoe is ESD-certified for extra protection of sensitive electronic equipment. Tested and approved for slip resistance. Unisex model.

CHARACTERISTICS	FUNCTIONS
• Excellent grip • Perfect fit • Extra comfortable • Excellent shock absorption • Light	• Low weight • Oil-resistant outsole • Anti-static properties • Double shock absorption zones • Conforms with IEC 61340-5-1 (ESD) • Water repellent leather



PREVENTS RISK OF

Sprain injuries, antistatic, slipping, strain injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, office environments, all-year use, slippery environments, dry environments, clean environments

PRIMARY AREAS OF USE

Electronics work, security- and police work, cleaning, hotel- and restaurant work, healthcare, care work, service work, office work

PRIMARY INDUSTRIES OF USE

Horeca, service, retail

SPECIFICATION

TYPE Occupational footwear, Low shoes

CATEGORY Cat. II

FITTING Regular

COLLECTION SpOc

UPPER MATERIAL Full-grain leather

LINING MATERIAL Polyester

INSOLE FX2 Pro SpOc

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL EVA

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Laces

SHOELACES LENGTH 100 cm


COLOUR Black

NET WEIGHT, (SIZE 42) 0.69 kg

COMPLIANCE



EN ISO 20347:2012
O2, A, E, FO, SRC



ASTM F2892-18
SD 35

TP TC 017:2011



ÖNORM Z 1259

FEATURES



Oil-resistant outsole



Anti-static properties



Ergothan Shock
Absorption System



ESD



Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	2½	4½	5342-35	6408487507496
36	3	3½	5	5342-36	6408487507502
37	4	4½	5½	5342-37	6408487507519
38	4½	5	6½	5342-38	6408487507526
39	5½	6	7	5342-39	6408487507533
40	6	6½	8	5342-40	6408487507540
41	7	7½	8½	5342-41	6408487507557
42	8	8½	9½	5342-42	6408487507564
43	9	9	10½	5342-43	6408487507571
44	10	9½	11	5342-44	6408487507588
45	10½	10½	12	5342-45	6408487507595
46	11	11½	12½	5342-46	6408487507601
47	12	12	13½	5342-47	6408487507618
48	13	13	14	5342-48	6408487507625

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com