



jalas® DRYLOCK 3318

EN ISO 20345:2022 S7, HRO    ASTM F2413-18 M/I/C SD 35 PR    ASTM F3445-21 SR



[Learn more](#)

A waterproof mid-cut safety boot with highest protection designed for comfort in cold environments. The grain leather and the durable textile upper protects feet and keeps them warm and features safety reflection strips. The oil and heat-resistant nitrile outer sole gives excellent grip and JALAS® aluminium toe cap, steel puncture protection and double impact protection zones in PORON® XRD® help keep feet safe in demanding conditions.

CHARACTERISTICS

- Excellent shock absorption
- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable

FUNCTIONS

- Reflector
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Ventilating insole
- Waterproof
- Quick-tie
- ProNose toe reinforcement
- Bellows tongue
- Waterproof Drylock-membrane



PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, environments with risk for outsole penetration, wet environments, harsh environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Steel

FITTING Regular

COLLECTION Drylock

UPPER MATERIAL Full-grain leather, Textile

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide, Drylock membrane

INSOLE JALAS 8217 FX2 Climate

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Laces

SHOELACES LENGTH 130 cm

COLOUR Black, Grey, Red

NET WEIGHT, (SIZE 42) 1.48 kg

COMPLIANCE



EN ISO 20345:2022  
S7, HRO



ASTM F2413-18  
M/I/C  
SD 35 PR

TP TC 019:2011

ASTM F3445-21  
SR



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock  
Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



ProNose toe  
reinforcement



Nail protection in steel



Heat-resistant outsole



Waterproof

| SIZE |     |      |      | ARTICLE<br>NUMBER | EAN           |
|------|-----|------|------|-------------------|---------------|
| EU   | UK  | US M | US W |                   |               |
| 36   | 3   | 4    | 5    | 3318-36           | 6408487427947 |
| 37   | 4   | 5    | 6    | 3318-37           | 6408487427954 |
| 38   | 5   | 5½   | 6½   | 3318-38           | 6408487427961 |
| 39   | 6   | 6½   | 7½   | 3318-39           | 6408487427978 |
| 40   | 6½  | 7½   | 8½   | 3318-40           | 6408487427985 |
| 41   | 7   | 8    | 9    | 3318-41           | 6408487427992 |
| 42   | 8   | 9    | 10   | 3318-42           | 6408487428005 |
| 43   | 9   | 9½   | 11   | 3318-43           | 6408487428012 |
| 44   | 10  | 10½  | 11½  | 3318-44           | 6408487428029 |
| 45   | 10½ | 11   | 12½  | 3318-45           | 6408487428036 |
| 46   | 11  | 12   | 13   | 3318-46           | 6408487428043 |
| 47   | 12  | 13   | 14   | 3318-47           | 6408487428050 |

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden  
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com