



jalas® EXALTER 9925

EN ISO 20345:2011 S1, P, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR



[Learn more](#)

LOW-CUT WITH VENTILATION AND BOA®

This low-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The midsole and JALAS FX3 Supreme multilayer insole together with the sock-like construction provide ultimate comfort. PORON® XRD™ shock-absorption prevents injuries to foot and back. The upper has net-covered ventilation holes to keep feet cool and prevent particles from entering the shoes. BOA® Fit System makes it easy to put on and take off the shoe.

CHARACTERISTICS

- Excellent grip
- Perfect fit
- Extra comfortable
- Very breathable
- Excellent shock absorption

FUNCTIONS

- Double shock absorption zones
- Anti-static properties
- Ventilating insole
- Heat-resistant outsole
- Oil-resistant outsole
- Breathable mesh
- Polstered shaft edge
- BOA® Fit System
- Ergonomically shaped
- Quick-tie
- Stabilizator
- Conforms with IEC 61340-5-1 (ESD)
- Soft
- Specially designed details
- Free from animal-derived materials



PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, dry environments, clean environments, warm environments

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE JALAS 8303 FX3 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black, Green

NET WEIGHT, (SIZE 42) 1.31 kg

COMPLIANCE



EN ISO 20345:2011
S1, P, SRC, HRO



ASTM F2413-18
M/I/C
SD 35 PR

TP TC 019:2011



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock
Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Nail protection in
plasma-treated
composite (PTC)
textile



Heat-resistant outsole



Stabilizer

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1½	2½	3½	9925-34	6408487513473
35	2	3½	4	9925-35	6408487513480
36	3	4	5	9925-36	6408487513497
37	4	5	6	9925-37	6408487513503
38	5	5½	6½	9925-38	6408487513510
39	6	6½	7½	9925-39	6408487513527
40	6½	7½	8½	9925-40	6408487513534
41	7	8	9	9925-41	6408487513541
42	8	9	10	9925-42	6408487513558
43	9	9½	11	9925-43	6408487513565
44	10	10½	11½	9925-44	6408487513572
45	10½	11	12½	9925-45	6408487513589
46	11	12	13	9925-46	6408487513596
47	12	13	14	9925-47	6408487513602

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com