



jalas® EXALTER 9935

EN ISO 20345:2022 S1, PS, HRO, FO, SC ASTM F2413-18 M/I/C SD 35 PR



Learn more

NEW SUSTAINABLE GENERATION

Exalter’s new generation is upgraded with several recycled and bio-based materials without compromising the superior combination of durability, comfort, and lightness that users have relied on for years. Bio-based microfiber upper with mesh-covered ventilation slots. BOA® Fit System (from recycled material) on the side eliminates pressure points. Aluminum toe cap and recycled metal-free nail protection insert with high-grip Vibram® recycled nitrile rubber outsole.

CHARACTERISTICS

- Excellent grip
- Extra comfortable
- Excellent shock absorption
- Very breathable

FUNCTIONS

- Double shock absorption zones
- Anti-static properties
- Ventilating insole
- Heat-resistant outsole
- Oil-resistant outsole
- Breathable mesh
- Polstered shaft edge
- BOA® Fit System
- Ergonomically shaped
- Quick-tie
- Stabilizator
- Conforms with IEC 61340-5-1 (ESD)
- Soft
- Specially designed details
- Free from animal-derived materials



PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors, all-year use, warm surfaces, environments with risk for outsole penetration, slippery environments, dry environments, clean environments, warm environments

PRIMARY AREAS OF USE

Agricultural work, assembly, building and construction, carpentry, concrete work, construction, engineering, gardening, inspection work, installation work, machine driving, machine operating, paper industry work, repair work, transport work, warehouse work, wood industry work

PRIMARY INDUSTRIES OF USE

Agriculture, pulp and paper, rubber and plastic, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL EcoFlex Zero perforation textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE JALAS 8304 FX3 Soft

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black, Yellow

NET WEIGHT, (SIZE 42) 1.23 kg

COMPLIANCE



TP TC 019:2011



EN ISO 20345:2022
S1, PS, HRO, FO, SC



ASTM F2413-18
M/II/C
SD 35 PR

FEATURES



Aluminium toecap



Nail protection in
plasma-treated
composite (PTC)
textile



Oil-resistant outsole



Ergothan Shock
Absorption System



Stabilizer



Anti-static properties



ESD



Heat-resistant outsole

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1½	2½	3½	9935-34	6408487513022
35	2	3½	4	9935-35	6408487513039
36	3	4	5	9935-36	6408487513046
37	4	5	6	9935-37	6408487513053
38	5	5½	6½	9935-38	6408487513060
39	6	6½	7½	9935-39	6408487513077
40	6½	7½	8½	9935-40	6408487513084
41	7	8	9	9935-41	6408487513091
42	8	9	10	9935-42	6408487513107
43	9	9½	11	9935-43	6408487513114
44	10	10½	11½	9935-44	6408487513121
45	10½	11	12½	9935-45	6408487513138
46	11	12	13	9935-46	6408487513145
47	12	13	14	9935-47	6408487513152

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com