



A safety shoe with many features. Perfect for those who work in moist environments.

# Jalas EXALTER 9965

EN ISO 20345:2011 S3, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR

## LOW-CUT, WATER REPELLANT WITH BOA®

This low-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The multilayer insole together with the sock-like construction provide ultimate comfort. PORON<sup>®</sup> XRD<sup>™</sup> shock-absorption prevents injuries to foot and back. The upper is water repellant, perfect for those who work in moist environments. BOA<sup>®</sup> Fit System makes it easy to put on and take off the shoe.

### CHARACTERISTICS

- г
- Excellent shock absorption
- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable

### FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Ventilating insole
- BOA<sup>®</sup> Fit System
- Double shock absorption zones
- Heat-resistant outsole
- Water repellent
- Polstered shaft edge
- Ergonomically shaped
- Conforms with IEC 61340-5-1 (ESD)
- Quick-tie
- Stabilizator
- Soft





DIALED IN. PRECISION FIT.



Specially designed details

Free from animal-derived materials

# ■jalas® EXALTER 9965

### PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

### PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, clean environments

### SPECIFICATION

TYPE Safety footwear, Low shoes CATEGORY Cat. II NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile FITTING Regular **COLLECTION** Exalter UPPER MATERIAL Microfiber, Textile **TOECAP MATERIAL** Aluminium LINING MATERIAL Polyester INSOLE JALAS 8303 FX3 Supreme INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, PORON<sup>®</sup> XRD<sup>®</sup> MIDSOLE MATERIAL PU midsole OUTSOLE MATERIAL Nitrile rubber outsole FASTENING BOA Fit System COLOUR Black, Red NET WEIGHT, (SIZE 42) 1.28 kg

#### COMPLIANCE **C F** Cat. II FAL TP TC 019:2011 ASTM F2413-18 EN ISO 20345:2011 ÖNORM Z 1259 S3, SRC, HRO M/I/C SD 35 PR DGUV 112-191 DGU FEATURES Anti-static properties Ergothan Shock ESD Absorption System Oil-resistant outsole Nail protection in Aluminium toecar plasma-treated composite (PTC) textile

Water repellent

Stabilizator

Heat-resistant outsole

\*

SIZE				ARTICLE	
EU	UK	US M	US W	NUMBER	EAN
34	11/2	21/2	31⁄2	9965-34	6408487512575
35	2	31/2	4	9965-35	6408487512582
36	3	4	5	9965-36	6408487512599
37	4	5	6	9965-37	6408487512605
38	5	51/2	61⁄2	9965-38	6408487512612
39	6	61⁄2	71/2	9965-39	6408487512629
40	61⁄2	71/2	8 <sup>1</sup> /2	9965-40	6408487512636
41	7	8	9	9965-41	6408487512643
42	8	9	10	9965-42	6408487512650
43	9	91⁄2	11	9965-43	6408487512667
44	10	101/2	111⁄2	9965-44	6408487512674
45	101/2	11	121/2	9965-45	6408487512681
46	11	12	13	9965-46	6408487512698
47	12	13	14	9965-47	6408487512704



Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com