



jalas® EXALTER 9988 GTX

EN ISO 20345:2011 S3, SRC, WR, HRO ASTM F2413-18 M/I/C SD 35 PR ASTM F3445-21 SR



Learn more

A MID-CUT SAFETY SHOE, NOW WITH GORE-TEX

A light, comfortable, safety shoe with side-mounted BOA®. Waterproof due to GORE-TEX. Its Microfiber upper and sock-like construction provides great comfort and fit and has anti-static properties. The nitrile outer sole is heat and oil resistant for outstanding grip. It features also our JALAS® aluminium toe cap, plasma-treated textile puncture protection and double impact protection zones in PORON® XRD®.

CHARACTERISTICS

- Excellent shock absorption
- Perfect fit
- Extra comfortable
- High level of protection
- Excellent grip

FUNCTIONS

- Anti-static properties
- Ventilating insole
- Heat-resistant outsole
- Oil-resistant outsole
- Specially designed details
- Double shock absorption zones
- Polstered shaft edge
- BOA® Fit System
- GORE-TEX Performance Comfort Footwear technology
- Quick-tie
- Stabilizator
- Waterproof
- Ergonomically shaped
- Soft
- Conforms with IEC 61340-5-1 (ESD)
- Free from animal-derived materials



DIALED IN.
PRECISION FIT.

PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, environments with risk for outsole penetration, wet environments, moist environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyamide

INSOLE JALAS 8303 FX3 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black

NET WEIGHT, (SIZE 42) 1.33 kg

COMPLIANCE



Cat. II

EN ISO 20345:2011
S3, SRC, WR, HRO



ASTM F2413-18
M/I/C
SD 35 PR

TP TC 019:2011

ASTM F3445-21
SR



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock
Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Nail protection in
plasma-treated
composite (PTC)
textile



Heat-resistant outsole



Stabilizator



Waterproof

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1½	2½	3½	9988-34	6408487534324
35	2	3½	4	9988-35	6408487534362
36	3	4	5	9988-36	6408487534409
37	4	5	6	9988-37	6408487534447
38	5	5½	6½	9988-38	6408487534485
39	6	6½	7½	9988-39	6408487534522
40	6½	7½	8½	9988-40	6408487534560
41	7	8	9	9988-41	6408487534607
42	8	9	10	9988-42	6408487534645
43	9	9½	11	9988-43	6408487534683
44	10	10½	11½	9988-44	6408487534720
45	10½	11	12½	9988-45	6408487534768
46	11	12	13	9988-46	6408487534805
47	12	13	14	9988-47	6408487534843

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com