



Provides ankle support, extended impact protection and enhanced breathability.

Jalas° EXALTER 9945

EN ISO 20345:2011 S1, P, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR

MID-CUT WITH VENTILATION AND BOA®

This mid-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The model provides extra ankle support and PORON[®] XRD[™] shock-absorption prevents injuries to foot and back. The upper has net-covered ventilation holes to keep feet cool and prevent sand from entering the shoes. BOA[®] Fit System makes it easy to put on and take off the shoe.

CHARACTERISTICS	FUNCTIONS	
 Excellent grip Perfect fit Extra comfortable Very breathable Excellent shock absorption 	 Anti-static properties Ventilating insole Heat-resistant outsole Oil-resistant outsole Specially designed details Double shock absorption zones Breathable mesh Polstered shaft edge BOA[*] Fit System Quick-tie Stabilizator Ergonomically shaped Soft 	 Conforms with IEC 61340-5-1 (ESD) Free from animal-derived materials Ankle support





DIALED IN. PRECISION FIT.



PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, dry environments, clean environments, warm environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots CATEGORY Cat. II NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile FITTING Regular **COLLECTION** Exalter UPPER MATERIAL Microfiber, Textile **TOECAP MATERIAL** Aluminium LINING MATERIAL Polyester INSOLE JALAS 8303 FX3 Supreme INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Merino wool, Neo foam, PORON[®] XRD[®] MIDSOLE MATERIAL PU midsole OUTSOLE MATERIAL Nitrile rubber outsole FASTENING BOA Fit System COLOUR Black, Green NET WEIGHT, (SIZE 42) 1.31 kg

COMPLIANCE **C F** Cat. II FAL TP TC 019:2011 ASTM F2413-18 EN ISO 20345:2011 ÖNORM Z 1259 S1, P. SRC, HRO M/I/C SD 35 PR DGUV 112-191 DGU FEATURES Anti-static properties Ergothan Shock ESD Absorption System Oil-resistant outsole Nail protection in Aluminium toecar plasma-treated composite (PTC) textile Heat-resistant outsole Stabilizator

*

SIZE			ARTICLE	EAN	
EU	UK	US M	US W	NUMBER	EAN
34	11/2	21/2	31⁄2	9945-34	6408487512872
35	2	31/2	4	9945-35	6408487512889
36	3	4	5	9945-36	6408487512896
37	4	5	6	9945-37	6408487512902
38	5	51/2	61⁄2	9945-38	6408487512919
39	6	61⁄2	71/2	9945-39	6408487512926
40	61/2	71/2	8 ¹ /2	9945-40	6408487512933
41	7	8	9	9945-41	6408487512940
42	8	9	10	9945-42	6408487512957
43	9	91⁄2	11	9945-43	6408487512964
44	10	101/2	111/2	9945-44	6408487512971
45	101/2	11	121/2	9945-45	6408487512988
46	11	12	13	9945-46	6408487512995
47	12	13	14	9945-47	6408487513008

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

Limavägen 28, SE-793 32 Leksand, Sweden

ejendals.com