



A tough, mid-cut safety boot with highest protection level (S3) and BOA® Fit System built for heavy work.

jalas® HEAVY DUTY 1278

EN ISO 20345:2022 S3, HRO, CI, HI, FO, SC, LG ASTM F2413-18 M/I/C SD 35 PR



Learn more

A tough, mid-cut safety boot with highest protection level (S3) and BOA® Fit System built for heavy work. The PU-coated leather and microfibre upper gives excellent foot protection and additional ankle support. The oil and heat-resistant nitrile outer sole gives excellent grip, and JALAS® Composite Toe Cap, nail protection in steel and double impact protection zones in PORON® XRD® mean safer workdays.

CHARACTERISTICS

- Excellent shock absorption
- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable

FUNCTIONS

- ProNose toe reinforcement
- Pull loops
- Water repellent
- Heat-resistant outsole
- Oil-resistant outsole
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- BOA® Fit System
- Ankle support
- Ergonomically shaped
- Bellows tongue
- TPU heel support
- Padded shaft edge in memory foam



PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, oily and greasy environments, dirty environments, harsh environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Steel

FITTING Regular

COLLECTION Heavy Duty

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Composite

LINING MATERIAL Polyester, polyamide

INSOLE JALAS 8217 FX2 Climate

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black, Blue

NET WEIGHT, (SIZE 42) 1.4 kg

COMPLIANCE



EN ISO 20345:2022
S3, HRO, CI, HI, FO, SC, LG



ASTM F2413-18
M/I/C
SD 35 PR

TP TC 019:2011



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Oil-resistant outsole



ProNose toe reinforcement



ESD



Composite toecap



Ergothon Shock Absorption System



Nail protection in steel



Heat-resistant outsole



Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1278-35	6408487506086
36	3	4	5	1278-36	6408487506093
37	4	5	6	1278-37	6408487506109
38	5	5½	6½	1278-38	6408487506116
39	6	6½	7½	1278-39	6408487506123
40	6½	7½	8½	1278-40	6408487506130
41	7	8	9	1278-41	6408487506147
42	8	9	10	1278-42	6408487506154
43	9	9½	11	1278-43	6408487506161
44	10	10½	11½	1278-44	6408487506178
45	10½	11	12½	1278-45	6408487506185
46	11	12	13	1278-46	6408487506192
47	12	13	14	1278-47	6408487506208
48	13	13½	14½	1278-48	6408487506215

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com