



 GRAN PREMIO 1550 LOW

EN ISO 20345:2022 S2, HRO, CI, A



[Learn more](#)

EASY-TO-CLEAN LOAFER

Easy-to-clean safety loafer in specially treated leather with heat resistance para-aramid thread in the seams provides a max operating heat limit of 400°C/752°F for 30 minutes. Suitable for metal work, welding and other occasions when an easy cleaned upper is needed. Spacious last, toe cap in aluminium.

CHARACTERISTICS

- Excellent shock absorption
- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable

FUNCTIONS

- ProNose toe reinforcement
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Water repellent
- Double shock absorption zones
- Conforms with IEC 61340-5-1 (ESD)
- Ventilating insole
- Polstered shaft edge



PREVENTS RISK OF

Toe injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, warm surfaces

PRIMARY AREAS OF USE

Sheet-metal work, metalwork, welding, hot work

PRIMARY INDUSTRIES OF USE

Metal fabrication

SPECIFICATION

TYPE Safety footwear, Loafers

CATEGORY Cat. II

FITTING Wide

COLLECTION Gran Premio

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE JALAS 8103 FX2 Pro-X

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

COLOUR Black

NET WEIGHT, (SIZE 42) 1.17 kg

COMPLIANCE



EN ISO 20345:2022
S2, HRO, CI, A



ÖNORM Z 1259

TP TC 019:2011

DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock
Absorption System



ESD



Heat-resistant upper



Aluminium toecap



Oil-resistant outsole



ProNose toe
reinforcement



Wide fit



Heat-resistant outsole



Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1550-36	6408487442476
37	4	5	6	1550-37	6408487442483
38	5	5½	6½	1550-38	6408487442490
39	6	6½	7½	1550-39	6408487442506
40	6½	7½	8½	1550-40	6408487442513
41	7	8	9	1550-41	6408487442520
42	8	9	10	1550-42	6408487442537
43	9	9½	11	1550-43	6408487442544
44	10	10½	11½	1550-44	6408487442551
45	10½	11	12½	1550-45	6408487442568
46	11	12	13	1550-46	6408487442575
47	12	13	14	1550-47	6408487442582
48	13	13½	14½	1550-48	6408487442599

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com