



The XRD® M-Guard on the top is for those in need of extra protection.

 GRAN PREMIO 1938 GP META

EN ISO 20345:2011 S3, SRC, HRO, M, CI, HI ASTM F2413-18 M/I/C Mt SD 35 PR ASTM F3445-21 SR



WITH METATARSAL IMPACT PROTECTION

A new boot with integrated impact protection of the metatarsal part of the foot, using XRD® M-Guard. It is a high-tech material that is soft and flexible under normal conditions but hardens and absorbs up to 90% of the energy upon impact. For those in need of extra protection in demanding environments, this is an important function to decrease the risk for injuries to the upper foot. The shoes have a roomier fit for extra comfort, toe cap and nail penetration insert.

CHARACTERISTICS	FUNCTIONS	
• Perfect fit • Excellent shock absorption • High level of protection	• ProNose toe reinforcement • Pull loops • Ventilating insole • Heat-resistant outsole • Oil-resistant outsole • Padded boot shaft • Easy clean upper • Double shock absorption zones • Conforms with IEC 61340-5-1 (ESD) • Bellows tongue • Metatarsal protection with integrated PORON® XRD® • Polstered shaft edge	• Ankle support • ESD • Antistatic/ATEX • Water repellent leather • Heat insulating • Shock absorbing



PREVENTS RISK OF

Toe injuries, nail penetration, metatarsal injuries, antistatic, contact with cold, slipping, strain injuries

PRIMARY ENVIRONMENTS OF USE

Oily and greasy environments, dirty environments, harsh environments, environments with explosive risks

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Steel

FITTING Wide

COLLECTION Gran Premio

UPPER MATERIAL PU-coated leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyamide

INSOLE JALAS 8103 FX2 Pro-X

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING Laces

SHOELACES LENGTH 150 cm

COLOUR Black, Yellow

NET WEIGHT, (SIZE 42) 1.51 kg

COMPLIANCE



EU Regulation 2016/425



EN ISO 20345:2011
S3, SRC, HRO, M, CI, HI

TP TC 019:2011

ASTM F2413-18
M/II/C
Mt SD 35 PR

ASTM F3445-21
SR



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothon Shock
Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



ProNose toe
reinforcement



Wide fit



Heat-resistant outsole



Water repellent



Nail protection in steel

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3½	4	1938-35	6408487536120
36	3	4	5	1938-36	6408487536168
37	4	5	6	1938-37	6408487536205
38	5	5½	6½	1938-38	6408487536243
39	6	6½	7½	1938-39	6408487536281
40	6½	7½	8½	1938-40	6408487536328
41	7	8	9	1938-41	6408487536366
42	8	9	10	1938-42	6408487536403
43	9	9½	11	1938-43	6408487536441
44	10	10½	11½	1938-44	6408487536489
45	10½	11	12½	1938-45	6408487536526
46	11	12	13	1938-46	6408487536564
47	12	13	14	1938-47	6408487536601
48	13	13½	14½	1938-48	6408487536649
49	14	14½	15½	1938-49	6408487536687
50	15	15½	16½	1938-50	6408487536724

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com