



 TIO 2058

EN ISO 20345:2011 S1, P, SRC    ASTM F2413-18 M/I/C SD 35 PR



[Learn more](#)

THREE IN ONE SOLE. HIGH BREATHABILITY

A breathable safety shoe with high-quality protection. Ultimate softness and comfort thanks to the TIO (Three In One) sole that prevents long term injuries to the feet and back. The net-covered ventilation slots provide extra cooling. The Tri-Panel BOA® Fit System enables a perfect fit for individually shaped feet. The shoe has an aluminium toe cap and soft textile nail-penetration insert. The new Three in One sole technology is developed by Jalas.

CHARACTERISTICS

- Excellent grip
- Perfect fit
- Extra comfortable
- Very breathable
- Excellent shock absorption

FUNCTIONS

- Ergonomically shaped
- Oil-resistant outsole
- Anti-static properties
- Conforms with IEC 61340-5-1 (ESD)
- Ventilating insole
- Double shock absorption zones
- Soft
- BOA® Fit System
- ESD
- Anatomically designed
- Shock absorbing
- Free from animal-derived materials



ComSoft Air

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic, slipping

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, environments with risk for outsole penetration, slippery environments, dry environments, clean environments, warm environments

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION TIO

UPPER MATERIAL CPU overmolding, Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE JALAS 8304 FX3 Soft

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, PU, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL RPU outsole

FASTENING BOA® Fit System

COLOUR Black, Yellow

COMPLIANCE



EN ISO 20345:2011  
S1, P, SRC



ASTM F2413-18  
M/I/C  
SD 35 PR

TP TC 019:2011



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock  
Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Nail protection in  
plasma-treated  
composite (PTC)  
textile

| SIZE |     |      |      | ARTICLE<br>NUMBER | EAN           |
|------|-----|------|------|-------------------|---------------|
| EU   | UK  | US M | US W |                   |               |
| 35   | 2   | 3½   | 4    | 2058-35           | 6408487537363 |
| 36   | 3   | 4    | 5    | 2058-36           | 6408487537400 |
| 37   | 4   | 5    | 6    | 2058-37           | 6408487537448 |
| 38   | 5   | 5½   | 6½   | 2058-38           | 6408487537486 |
| 39   | 6   | 6½   | 7½   | 2058-39           | 6408487537523 |
| 40   | 6½  | 7½   | 8½   | 2058-40           | 6408487537561 |
| 41   | 7   | 8    | 9    | 2058-41           | 6408487537608 |
| 42   | 8   | 9    | 10   | 2058-42           | 6408487537646 |
| 43   | 9   | 9½   | 11   | 2058-43           | 6408487537684 |
| 44   | 10  | 10½  | 11½  | 2058-44           | 6408487537721 |
| 45   | 10½ | 11   | 12½  | 2058-45           | 6408487537769 |
| 46   | 11  | 12   | 13   | 2058-46           | 6408487537806 |
| 47   | 12  | 13   | 14   | 2058-47           | 6408487537844 |
| 48   | 13  | 13½  | 14½  | 2058-48           | 6408487537882 |

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden  
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com