



TEGERA® 450



[Learn more](#)

CUT AND HEAT PROTECTION COMBINED

Glove with high CRF cut protection for versatile assembly work. Knitted with 13gg CRF® Technology for solid cut C performance. Durable nitrile foam coating on palm for improved grip performance. Dirt-masking dark grey and black allow for extended product life. Withstands contact heat up to 100°C.

CHARACTERISTICS	FUNCTIONS
• Flexible • Durable • Good grip • Comfortable	• Withstands contact heat up to 100°C



PREVENTS RISK OF

Cut injuries, abrasion injuries, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Assembly, inspection work, engineering

PRIMARY INDUSTRIES OF USE

Metal fabrication, machinery and equipment, mro, automotive

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

LINING MATERIAL 13 gg, CRF® Technology, Glass fibre thread, HPPE, Nylon, Polyester, Spandex

LENGTH 220-270 mm

DEXTERITY 5

GRIP DESIGN Smooth finish

COLOUR Black

PAIRS PER: BUNDLE/CARTON 12/120

DISPLAY TYPE Bag with euro slot

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) TDM: 13.4 N

INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Glass fibre thread, Polyester, Nylon, Elastane

OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE



TP TC 019:2011



EN 407:2020 (No flame protection)
X1XXXX



EN 388:2016+A1:2018
4X44C

EN ISO 21420:2020



Contact heat rating valid for palm area only

FEATURES



Cut protection

SIZE		ARTICLE NUMBER	EAN
5	XXS	450-5	7340118445830
6	XS	450-6	7340118310558
7	S	450-7	7392626073319
8	M	450-8	7392626073333
9	L	450-9	7392626073357
10	XL	450-10	7392626073272
11	XXL	450-11	7392626073296

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com