



Provides ankle support, extended impact protection and enhanced breathability.

## Jalas EXALTER 9945

EN ISO 20345:2011 S1, P, SRC, HRO ASTM F2413-18 M/I/C SD 35 PR

# MID-CUT WITH VENTILATION AND BOA®

This mid-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The model provides extra ankle support and PORON<sup>®</sup> XRD<sup>™</sup> shock-absorption prevents injuries to foot and back. The upper has net-covered ventilation holes to keep feet cool and prevent sand from entering the shoes. BOA<sup>®</sup> Fit System makes it easy to put on and take off the shoe.

CHARACTERISTICS	FUNCTIONS	
<ul> <li>Excellent grip</li> <li>Perfect fit</li> <li>Extra comfortable</li> <li>Very breathable</li> <li>Excellent shock absorption</li> </ul>	<ul> <li>Anti-static properties</li> <li>Ventilating insole</li> <li>Heat-resistant outsole</li> <li>Oil-resistant outsole</li> <li>Specially designed details</li> <li>Double shock absorption zones</li> <li>Breathable mesh</li> <li>Polstered shaft edge</li> <li>BOA<sup>*</sup> Fit System</li> <li>Quick-tie</li> <li>Stabilizator</li> <li>Ergonomically shaped</li> <li>Soft</li> </ul>	<ul> <li>Conforms with IEC 61340-5-1 (ESD)</li> <li>Free from animal-derived materials</li> <li>Ankle support</li> </ul>





DIALED IN. PRECISION FIT.



### PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

### PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, dry environments, clean environments, warm environments

### SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots CATEGORY Cat. II NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile FITTING Regular **COLLECTION** Exalter UPPER MATERIAL Microfiber, Textile **TOECAP MATERIAL** Aluminium LINING MATERIAL Polyester INSOLE JALAS 8303 FX3 Supreme INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Merino wool, Neo foam, PORON<sup>®</sup> XRD<sup>®</sup> MIDSOLE MATERIAL PU midsole OUTSOLE MATERIAL Nitrile rubber outsole FASTENING BOA Fit System COLOUR Black, Green NET WEIGHT, (SIZE 42) 1.31 kg

#### COMPLIANCE **C F** Cat. II FAL TP TC 019:2011 ASTM F2413-18 EN ISO 20345:2011 ÖNORM Z 1259 S1, P. SRC, HRO M/I/C SD 35 PR DGUV 112-191 DGU FEATURES Anti-static properties Ergothan Shock ESD Absorption System Oil-resistant outsole Nail protection in Aluminium toecar plasma-treated composite (PTC) textile Heat-resistant outsole Stabilizator

\*

SIZE			ARTICLE	EAN	
EU	UK	US M	US W	NUMBER	EAN
34	11/2	21/2	31⁄2	9945-34	6408487512872
35	2	31⁄2	4	9945-35	6408487512889
36	3	4	5	9945-36	6408487512896
37	4	5	6	9945-37	6408487512902
38	5	51/2	61⁄2	9945-38	6408487512919
39	6	61⁄2	71/2	9945-39	6408487512926
40	61⁄2	71/2	81/2	9945-40	6408487512933
41	7	8	9	9945-41	6408487512940
42	8	9	10	9945-42	6408487512957
43	9	91⁄2	11	9945-43	6408487512964
44	10	101/2	111/2	9945-44	6408487512971
45	101/2	11	121/2	9945-45	6408487512988
46	11	12	13	9945-46	6408487512995
47	12	13	14	9945-47	6408487513008

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

Limavägen 28, SE-793 32 Leksand, Sweden

ejendals.com