



A safety shoe with many features. Perfect for those who work in moist environments.

jalas® EXALTER 9965

EN ISO 20345:2011 S3, SRC, HRO    ASTM F2413-18 M/I/C SD 35 PR



Learn more

LOW-CUT, WATER REPELLANT WITH BOA®

This low-cut safety shoe has the features you need for most work situations, such as PTC-textile nail protection, toecap in aluminum and high-grip Vibram Nitrile rubber outsole. The multilayer insole together with the sock-like construction provide ultimate comfort. PORON® XRD™ shock-absorption prevents injuries to foot and back. The upper is water repellant, perfect for those who work in moist environments. BOA® Fit System makes it easy to put on and take off the shoe.

CHARACTERISTICS

- Excellent shock absorption
- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable

FUNCTIONS

- Oil-resistant outsole
- Anti-static properties
- Ventilating insole
- BOA® Fit System
- Double shock absorption zones
- Heat-resistant outsole
- Water repellent
- Polstered shaft edge
- Ergonomically shaped
- Conforms with IEC 61340-5-1 (ESD)
- Quick-tie
- Stabilizator
- Soft
- Specially designed details
- Free from animal-derived materials



PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, clean environments

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE JALAS 8303 FX3 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black, Red

NET WEIGHT, (SIZE 42) 1.28 kg

COMPLIANCE



EN ISO 20345:2011  
S3, SRC, HRO



ASTM F2413-18  
M/I/C  
SD 35 PR

TP TC 019:2011



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock  
Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Nail protection in  
plasma-treated  
composite (PTC)  
textile



Heat-resistant outsole



Water repellent



Stabilizator

| SIZE |     |      |      | ARTICLE<br>NUMBER | EAN           |
|------|-----|------|------|-------------------|---------------|
| EU   | UK  | US M | US W |                   |               |
| 34   | 1½  | 2½   | 3½   | 9965-34           | 6408487512575 |
| 35   | 2   | 3½   | 4    | 9965-35           | 6408487512582 |
| 36   | 3   | 4    | 5    | 9965-36           | 6408487512599 |
| 37   | 4   | 5    | 6    | 9965-37           | 6408487512605 |
| 38   | 5   | 5½   | 6½   | 9965-38           | 6408487512612 |
| 39   | 6   | 6½   | 7½   | 9965-39           | 6408487512629 |
| 40   | 6½  | 7½   | 8½   | 9965-40           | 6408487512636 |
| 41   | 7   | 8    | 9    | 9965-41           | 6408487512643 |
| 42   | 8   | 9    | 10   | 9965-42           | 6408487512650 |
| 43   | 9   | 9½   | 11   | 9965-43           | 6408487512667 |
| 44   | 10  | 10½  | 11½  | 9965-44           | 6408487512674 |
| 45   | 10½ | 11   | 12½  | 9965-45           | 6408487512681 |
| 46   | 11  | 12   | 13   | 9965-46           | 6408487512698 |
| 47   | 12  | 13   | 14   | 9965-47           | 6408487512704 |

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden  
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com