



jalas® EXALTER 9988 GTX

EN ISO 20345:2011 S3, SRC, WR, HRO    ASTM F2413-18 M/I/C SD 35 PR    ASTM F3445-21 SR



Learn more

A MID-CUT SAFETY SHOE, NOW WITH GORE-TEX

A light, comfortable, safety shoe with side-mounted BOA®. Waterproof due to GORE-TEX. Its Microfiber upper and sock-like construction provides great comfort and fit and has anti-static properties. The nitrile outer sole is heat and oil resistant for outstanding grip. It features also our JALAS® aluminium toe cap, plasma-treated textile puncture protection and double impact protection zones in PORON® XRD®.

CHARACTERISTICS

- Excellent shock absorption
- Perfect fit
- Extra comfortable
- High level of protection
- Excellent grip

FUNCTIONS

- Anti-static properties
- Ventilating insole
- Heat-resistant outsole
- Oil-resistant outsole
- Specially designed details
- Double shock absorption zones
- Polstered shaft edge
- BOA® Fit System
- GORE-TEX Performance Comfort Footwear technology
- Quick-tie
- Stabilizator
- Waterproof
- Ergonomically shaped
- Soft
- Conforms with IEC 61340-5-1 (ESD)
- Free from animal-derived materials



PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, all-year use, environments with risk for outsole penetration, wet environments, moist environments

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber, Textile

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyamide

INSOLE JALAS 8303 FX3 Supreme

INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, PORON® XRD®

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black

NET WEIGHT, (SIZE 42) 1.33 kg

COMPLIANCE



EN ISO 20345:2011  
S3, SRC, WR, HRO



ASTM F2413-18  
M/I/C  
SD 35 PR

TP TC 019:2011

ASTM F3445-21  
SR



ÖNORM Z 1259



DGUV 112-191

FEATURES



Anti-static properties



Ergothan Shock  
Absorption System



ESD



Aluminium toecap



Oil-resistant outsole



Nail protection in  
plasma-treated  
composite (PTC)  
textile



Heat-resistant outsole



Stabilizator



Waterproof

| SIZE |     |      |      | ARTICLE<br>NUMBER | EAN           |
|------|-----|------|------|-------------------|---------------|
| EU   | UK  | US M | US W |                   |               |
| 34   | 1½  | 2½   | 3½   | 9988-34           | 6408487534324 |
| 35   | 2   | 3½   | 4    | 9988-35           | 6408487534362 |
| 36   | 3   | 4    | 5    | 9988-36           | 6408487534409 |
| 37   | 4   | 5    | 6    | 9988-37           | 6408487534447 |
| 38   | 5   | 5½   | 6½   | 9988-38           | 6408487534485 |
| 39   | 6   | 6½   | 7½   | 9988-39           | 6408487534522 |
| 40   | 6½  | 7½   | 8½   | 9988-40           | 6408487534560 |
| 41   | 7   | 8    | 9    | 9988-41           | 6408487534607 |
| 42   | 8   | 9    | 10   | 9988-42           | 6408487534645 |
| 43   | 9   | 9½   | 11   | 9988-43           | 6408487534683 |
| 44   | 10  | 10½  | 11½  | 9988-44           | 6408487534720 |
| 45   | 10½ | 11   | 12½  | 9988-45           | 6408487534768 |
| 46   | 11  | 12   | 13   | 9988-46           | 6408487534805 |
| 47   | 12  | 13   | 14   | 9988-47           | 6408487534843 |

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden  
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com